



Arak Petrochemical Company



ISO 9001:2000
Certificate No.: CH98/8032

ISO 14001:2004
Certificate No.: CH03/0112

OHSAS 18001:1999
Certificate No.: CH05/0675

Address:

No. 3, Taban St.
Vali-e-Asr Ave.
Tehran - IRAN

Tel:

(+98 21)82122700

Fax:

(+98 21)88674126-27

Web-site:

arpc-ir.com

E-mail:

sales@arpc-ir.com

Monoethanolamine (MEA)

Characteristic		Test Method	Unit	Value
PURITY		MA – 503 (GC)	WT. %	99 MIN.
WATER		ASTM D - 1364	WT. %	0.2 MAX.
COLOR Pt-Co	Steel drum	ASTM D - 1209	-	30 MAX.
	HDPE drum / ISO tank			10 MAX.
SP. GR (20/20 °C)		ASTM D - 891	-	1.017 - 1.019
EQUIVALENT MOL. WEIGHT		MA - 503	-	61 - 62.5

MONOETHANOLAMINE obtained from the reaction between ammonia and ethylene oxide. **MONOETHANOLAMINE**, have a low volatility at room temperature, is hygroscopic, presents an ammoniac odor and can appear in solid or liquid form depending on the temperature and the purity grade.

○ Application areas:

• Detergents :

MONOETHANOLAMINE, recommended as a component in detergent formulations for laundry and dishwashing, degreasers, multiple use detergents and disinfectants.

MONOETHANOLAMINE can also be used as neutralizer agent in formulations of car wash shampoos, degreasers in general, wax removers and as corrosion inhibitors.

• Agrochemicals :

MONOETHANOLAMINE, used as neutralizer agent for anionic emulsifiers.

• Treatment of gases :

Ethanolamines can be used to treat natural gas and petroleum residual gas in the absorption of carbon dioxide. In gas systems containing carbon dioxide, **MONOETHANOLAMINE** can be used as a selective absorber, and plays an important role in the production of ammonia, liquid carbon dioxide and dry ice permitting regeneration in the latter cases.



ISO 9001:2000
Certificate No.: CH98/8032

ISO 14001:2004
Certificate No.: CH03/0112

OHSAS 18001:1999
Certificate No.: CH05/0675

Address:

No. 3, Taban St.
Vali-e-Asr Ave.
Tehran - IRAN

Tel:

(+98 21)82122700

Fax:

(+98 21)88674126-27

Web-site:

arpc-ir.com

E-mail:

sales@arpc-ir.com

Monoethanolamine (MEA)

• **Other uses :**

MONOETHANOLAMINE recommended as synthesis intermediate for the manufacture of corresponding alkanolamides due to its reaction with fatty acid or coconut oil. As a consequence of its properties, this product can be used in various industrial segments such as detergents, lubricant oils, products for hygiene and personal care, flotation of minerals, etc.

Ethanolamines can also be used in the formulation of pharmaceutical products, dispersing agents for glues, gums, latex and photographic developers, accelerators of rubber vulcanization, corrosion inhibitors, pH controllers, synthesis intermediates, lacquer, paint, wax and polisher wetting agents, polymerizing agents and catalysts for polyurethane resins.

○ **Storage conditions:**

Since this product is hygroscopic we recommend provide the tanks with an inert atmosphere such as of nitrogen to reduce the absorption of water and to avoid darkening through contact with the air. We recommend storing **MONOETHANOLAMINE**, by bulk in stainless steel 316 or 304 tanks, equipped with a water or vapor heating coil to maintain the products at a temperature above their solidification point.

○ **Packing:**

Bulk or in 220 Lit (net: 200 Kg) new drums, each 4 drums strapped on a pallet.